



# Modular Floodlight

## 120W

### Applications:

Residential and Commercial Applications.


- Coastal Grade 1100 coastal powder coated aluminium frame with 1060 pure aluminium radiating modules and hollowed out rivets serving as a heat sink.
- 316 3-part stainless steel bracket designed to decrease installation time whilst preventing rust and corrosion.
- High Power Philips 5050 SMD Chips with an efficacy of 160lm/W.
- 20°/90°/140°x100° (asymmetrical beam angle) optics available. (Standard @ 90°).
- 270° rotatable bracket with each module being able to tilt independently reducing light spillage.
- Built in 10kV surge protection allowing for use within the most demanding environments.
- Resistant to UV rays with a wide operating temperature of -40°C to 50°C.

### Product Performance


<b>Wattage</b>	120W
<b>Colour Temperature &amp; Stock Code</b>	5700K - <b>F028</b>
<b>Operating Temperature</b>	-20~40°C
<b>Life Span/ LB Rating</b>	L80B20>50000H
<b>IP Rating</b>	IP65
<b>LED Driver Brand</b>	Mean Well or Inventronics Driver
<b>Beam Angle</b>	90°
<b>Impact Protection Grade</b>	IK10
<b>Input Voltage</b>	AC180-277V
<b>Surge Protection</b>	10kV
<b>Power Factor</b>	0.95
<b>CRI</b>	>83
<b>Lumen Output</b>	19 200
<b>Lumen Efficiency</b>	160lm/W
<b>LED Chips</b>	Philips 5050
<b>LED Chips Qty</b>	46
<b>Dimmable</b>	Non-Dimmable
<b>Dimmable Range</b>	-
<b>(Dali/Trailing/Leading)</b>	-
<b>Physical Characteristics</b>	
<b>Weight (kg)</b>	2.9
<b>Housing Material</b>	Pure Aluminium
<b>Product Dimensions (mm)</b>	H 212 x L 310 x W 116
<b>Cable Length</b>	0.3
<b>Mounting Option</b>	-
<b>Bracket Material</b>	316 3-part Stainless Steel Bracket
<b>Bolts and Screws</b>	316 Stainless Steel

\*External 10kV Surge Protectors are included with all our Modular Floodlights from July 2022 onwards.


## Luminous Intensity Distribution Diagram



## Packaging



## Dimension Drawing



## Technical Parameters

<b>Input Current</b>	600mA
<b>Output Voltage</b>	48
<b>Flicker Free (Y/N)</b>	Yes
<b>Humidity</b>	40%~80%
<b>Frequency</b>	47-63hz
<b>In Rush Current</b>	65A MeanWell /147A Inventronics
<b>Output Current</b>	2.3A
<b>THD</b>	<20%
<b>TA &amp; TC</b>	TA=-20 ~45 °C/TC=65°C
<b>IES (Yes or No)</b>	Yes
Regulatory Qualifications	
<b>Class Rating</b>	Class I
<b>Energy Efficiency</b>	A
<b>Certification</b>	CE, EMC, IEC60958, RoHS, ISO9001
<b>Accessories</b>	
<b>Optional accessories</b>	Pole mount bracket - F025D 20° lens x 1(F025 to 29) - F025A 140*100° lens x 1(F025 to 29) - F025B

<b>Packaging info</b>	
<b>Storage Temp</b>	-40~+60°C
<b>Carton Size (mm)</b>	365*171*273
<b>QTY/CTN</b>	1
<b>Net Weight</b>	3
<b>Gross Weight</b>	3.5



**PIOLED**  
**LIGHTING**  
SINCE 2008

# Modular Accessories

## FO25D - Pole Holder D84

### Costal HD 20-240W

Aluminium and Stainless

Steel Bolts

211mm x 125mm x 75mm



**120W**



**240W**

