

# Kratos Linear Highbay

150W

## Applications:

Residential and Commercial Applications.

- Industrial Spec Philips 5700K LED Chips producing an effective 140lm/W.

- Specially designed optics 30°x90° or 90° available, the ultimate solution for high racking warehouse installations.

- Pure Aluminium Matt Black Powder Coated Housing providing quick and efficient heat dissipation.

- 1-10V Dimmable Driver with a built in 4kV Surge Protection for hassle free illumination.

- L80B10 @ 50 000 hours rated lifespan ensures maximum lumen output with minimal decay.

- Ideal for Cold rooms and Standard warehousing applications with a Working Temperature of -20°C ~ 40°C.


- IK08 Impact Resistance increasing the robustness of the luminaire.

- Suspension Kit included for a quick and easy installation.

## Product Performance

<b>Wattage</b>	150W
<b>Colour Temperature &amp; Stock Code</b>	5700K 30*90D <b>HBL007</b> 5700K 90D <b>HBL008</b>
<b>Operating Temperature</b>	-20~40°C
<b>Life Span/ LB Rating</b>	L80B10@50000hr
<b>IP Rating</b>	IP54
<b>LED Driver Brand</b>	PioLED High Spec Driver
<b>Beam Angle</b>	30°x90° or 90°
<b>Impact Protection Grade</b>	IK08
<b>Input Voltage</b>	100-277V
<b>Surge Protection</b>	4kV
<b>Power Factor</b>	0.9
<b>CRI</b>	>83
<b>Lumen Output</b>	21 000
<b>Lumen Efficiency</b>	140lm/W
<b>LED Chips</b>	2835 Philips
<b>LED Chips Qty</b>	216
<b>Dimmable</b>	Dimmable (1-10V)
<b>Dimmable Range</b>	-
<b>(Dali/Trailing/Leading)</b>	1-10V
<b>UGR</b>	15
<b>Physical Characteristics</b>	
<b>Weight (g)</b>	2140
<b>Housing Material</b>	Aluminium
<b>Product Dimensions (mm)</b>	730*129*70
<b>Cable Length</b>	43cm
<b>Mounting Option</b>	Bracket and Steel Rope
<b>Bracket Material</b>	Aluminium
<b>Bolts and Screws</b>	304 Stainless Steel


## Luminous Intensity Distribution Diagram



## Packaging



## Dimension Drawing



## Technical Parameters

**Input Current** 0.73A

**Output Voltage** 155

**Flicker Free (Y/N)** Yes

**Humidity** 10%~98%

**Frequency** 50-60hz

**In Rush Current** 50A

**Output Current** 920mA

**THD** <20%

**TA & TC** TA=45/TC=90

**IES (Yes or No)** Yes

## Regulatory Qualifications

**Class Rating** Class I

**Energy Efficiency** A

**Certification** CE, IEC60598, EMC, ErP, TM21

**Accessories**

**Optional accessories** 0.8m Stainless steel suspension kit included

**Packaging info**

**Storage Temp** -20~+70°C

**Carton Size (mm)** 795\*350\*330

**QTY/CTN** 6

**Net Weight** 12.8

**Gross Weight** 15.6